

# HUTCHINSON®

WORLDWIDE



# bullet proof wheels

**TTGA Pvt. Ltd**

80/1, Block-II, WHS, Kirti Nagar, New Delhi - 110015, India

Mobile: 9015253545

E-Mail: kapila@ttga.in

Website: www.ttga.in

## PRODUCT CATALOG

### RUNFLAT DEVICES: ENHANCED MOBILITY PROTECTION



*Hutchinson Variable Function Inserts are designed to fit inside the tire, out of sight and out of the way. They provide the ultimate in enhanced mobility protection allowing continued mobility in the event of an in transit emergency.*

### DESIGNED FOR THE CHEVY SUBURBAN



#### SPECS

size 16 x 8.0"  
bolt pattern 8H - 6.5" BCD  
hub bore diameter 4.595" (116.7 mm)  
lug style 60° conical  
SAE rated load 3305 lbs. - 80 psi  
backspacing 4.59" (116.5 mm)  
construction Forged aluminum alloy

**WA-0456**



#### SPECS

size 17.5 x 7.5"  
bolt pattern 8H - 6.5" BCD  
hub bore diameter 4.69" (119.1 mm)  
lug style flat base  
SAE rated load 5,000 lbs. - 125 psi  
backspacing 4.94" (125.5 mm)  
construction Turned aluminum alloy

**WA-0509**



#### SPECS

size 16 x 7.5"  
bolt pattern 8H - 6.5" BCD  
hub bore diameter 4.597" (116.8 mm)  
lug style 60° conical  
SAE rated load 3,600 lbs. - 80 psi  
backspacing 4.59" (116.6 mm)  
construction Forged aluminum alloy

**WA-0529**

### DESIGNED FOR THE TOYOTA LAND CRUISER



#### SPECS

size 16 x 8.0"  
bolt pattern 5H - 150 mm BCD  
hub bore diameter 4.355" (110.6 mm)  
lug style flat base  
SAE rated load 3415 lbs. - 80 psi  
backspacing 4.59" (116.5 mm)  
construction Forged aluminum alloy

**WA-0460**



#### SPECS

size 17 x 8.5"  
bolt pattern 6H - 150 mm BCD  
hub bore diameter 4.324" (109.8 mm)  
lug style flat base  
SAE rated load 3,200 lbs.  
backspacing 5.80" (147.4 mm)  
construction Cast aluminum alloy

**WA-0550**

### DESIGNED FOR FORD TRUCK/SUVS



#### SPECS

designed for Ford F-550 Chassis  
size 20 x 8.5"  
bolt pattern 10H - 225 mm BCD  
hub bore diameter 6.703"  
lug style flat base  
SAE rated load 6000 lbs. - 115 psi  
backspacing 6.67" (169.5 mm)  
construction Forged aluminum alloy

**WA-0590**



#### SPECS

designed for Ford Expedition  
size 17 x 7.5"  
bolt pattern 6H - 135 mm BCD  
hub bore diameter 3.423"  
lug style 60° conical  
SAE rated load 3,195 lbs. - 80 psi  
backspacing 4.85" (123.2 mm)  
construction Forged aluminum alloy

**WA-0429**



## SPECS

**size** 17 x 8.5"  
**bolt pattern** 6H - 5.5" BCD  
**lug style** 60° conical  
**hub bore diameter** 3.055" (77.6 mm)  
**SAE rated load** 3,200 lbs. - 60 psi  
**backspacing** 5.47" (138.9 mm)  
**construction** Cast aluminum alloy  
 Wheel assembly includes:

- Assembly studs and locking nuts
- O-ring seal
- Hub cover

**WA-0523**

## FIT LIST

Make	Model	Year	
GMC	Sierra	1500	2000 - 2004
	Yukon	4x4	2000 - 2004
	Denali		2001 - 2004
	C/K	1500	1988 - 1998
Chevy	Tahoe	4DR 4X2	2001 - 2004
	Suburban	1500	2000 - 2005
		1500 4x2 / 4x4	1971 - 1991
	Silverado	1500	2003 - 2004
		1500 LWB 4x4	1980 - 1987
Avalanche		2002 - 2004	
C/K	1500	1988 - 1998	
Cadillac	Escalade		2002 - 2005



## SPECS

**size** 17 x 8.5"  
**bolt pattern** 6H - 5.5" BCD  
**hub bore diameter** 4.168 (105.9 mm)  
**lug style** flat base  
**SAE rated load** 2750 lbs. - 60 psi  
**backspacing** 5.47" (138.9 mm)  
**construction** Cast aluminum alloy  
 Wheel assembly includes:

- Assembly studs and locking nuts
- O-ring seal
- Hub cover

**WA-0558**

## FIT LIST

Make	Model	Year		
Toyota	Tundra		1999 - 2005	
	4Runner		1990 - 1998	
		Limited		1996 - 2002
		SR5		1996 - 1998
	Tacoma	4x4		1995 - 2005
Sequoia			2000 - 2005	



## SPECS

**size** 17 x 8.5"  
**bolt pattern** 8H - 6.69" BCD  
**hub bore diameter** 4.931" (125.2 mm)  
**lug style** flat base  
**SAE rated load** 3,200 lbs. - 60 psi  
**backspacing** 5.28" (134.2 mm)  
**construction** Cast aluminum alloy  
 Wheel assembly includes:

- Assembly studs and locking nuts
- O-ring seal
- Hub cover

**WA-0539**

## FIT LIST

Make	Model	Year	
Ford	Excursion		2000 - 2004
	F250	HD/SD	1999 - 2005



## SPECS

**size** 17 x 8.5"  
**bolt pattern** 8H - 6.5" BCD  
**hub bore diameter** 4.595 (116.7 mm)  
**lug style** 60° conical  
**SAE rated load** 3,200 lbs. - 60 psi  
**backspacing** 5.28" (134.2 mm)  
**construction** Cast aluminum alloy  
 Wheel assembly includes:

- Assembly studs and locking nuts
- O-ring seal
- Hub cover

**WA-0549**

## FIT LIST

Make	Model	Year		
GMC	Sierra	2500 HD	2001 - 2004	
	C/K	2500	1988 - 1998	
		3500	1995 - 1998	
	HUMMER	H1		1996 - 2002
		H2		2003 - 2004
Chevy	Silverado	1500 HD	2002	
	Suburban	2500 HD	2000 - 2004	
		3500 HD	1999 - 2005	
		2500	2000 - 2004	
	Avalanche	2500	2002 - 2004	
	Yukon	Yukon 2500		2003 - 2004
		C/K	2500 LWB	2003 - 2004
			3500 LWB	2003 - 2004
		3500 4DR Dual		1995 - 1998